New

Economical Spring Rewind Hose Reel HR65SR



The HR65SR is a high performance spring rewind hose reel constructed of heavy gauge powder coated steel for use in most low/medium and high pressure cold water applications. The 4-position roller guide arm adjusts for wall, overhead or ceiling mounting positions.

All reels come supplied with 65 feet of high pressure wire braided hose installed on the reel, with hose stop.

| Inlet/Outlet | Working pressure | Hose ID | Hose Length | Dim W X H X D | <u>Weight</u> |
|--------------|------------------|---------|-------------|----------------------|---------------|
| 3/8 " | 4000 PSI | 3/8" | 65 feet | 9.1" x 20.5" x 22.8" | 66 lbs |

Features

- Heavy gauge steel frame includes dramatically flanged edges and stiffening ribs for lighter weight, stronger components for ease of handling and installation.
- Maximum working pressure 4000 psi.
- For use in cold water applications
- Maximum temp. 210 F / 100 C
- 7 inch wide L-Shaped base with groove reinforcement ensure stable support
- Corrosion resistant powder coating
- Guide arm adjustable handling up to 9 positions
- Multi-position ratchet lock
- Solid 1" steel axle
- Enclosed drive spring eliminates possibility of damage
- Easy to mount base can be mounted on wall, ceiling or floor
- All brass swivel assembly
- ALL reels come with 65 feet of high pressure wire
- braided hose factory installed , with hose stop !



Repair Parts Available

| Roller Assembly | HR65SRRK001 |
|------------------|-------------|
| Ratchet assembly | HR65SRRK002 |
| Drum assembly | HR65SRRK003 |
| Swivel assembly | HR65SRRK005 |
| Hose Stop | HR65SRRK006 |

1551, rue De Coulomb, bureau 110, Boucherville, Québec J4B 8J7 Tel : 1.866.641.6633 Fax : 450.641.2633 www.multipsi.com / www.multipsi.com